
Shedology 101





**This diagram shows commonly referred to components and does not show all components that may make up a building. This is a generic diagram and it is important to remember all builders/brands construct their buildings differently. If you have a question regarding a particular component please reach out to your local sales rep, check out the models additional specifications on our website, or call us (270) 789 - 4236.

Additional Specifications Superior - Utility

Wall Specs		
Wall Height	6' 4" Wall Height (Approx 76.5")	
Stud Type	2"x4"	
Stud Spacing	16" o.c	
Siding	5/8" Premium Quality T-111 Siding	
Trim	Treated Trim Board	
Sheathing	None	
Vents	(2) 8"x16" metal vents placed at each gable & roof ridge vent.	

Roof Specs				
Roof Pitch	4/12			
Rafter Type	2"x4"			
Rafter Spacing	16" o.c			
Roof Type	Mac Metals - Mac Life (A) WeatherXL 29 Gauge or 3D Architectural Shingles			
Sheathing	7/16" OSB			

Floor Specs			
Joist Type	8' & 12' Wide - 2'x4' / 10' & 14' Wide -2'x6'		
Joist Spacing	16" o.c		
Flooring	3/4" Tongue & Groove "Advantech" or its equivalent		
Runners	4"x6" Pressure Treated Runners, Notched		
	8' & 10' Wide - 2 Runners / 12' & 14' Wide - 4 Runners		



Additional Specifications Superior - Utility

Door Specs				
Standard Door	8' Wide - 5' Double Doors / 10' Wide & Wider - 6' Double Doors			
Door Opening	5' Double Doors - Approx 60"x72" / 6' Double Doors - Approx 72"x72"			
Threshold	Heavy Duty Aluminum Diamond Plate			

Standard Features	





Cedar Naturaltone

